

AMENDMENTS TO THE CLAIMS:

Please cancel claims 1, 2, 6, 7, and 17-22 without prejudice or disclaimer.

1-2. (Canceled).

3. (Previously presented) A demultiplexing method of receiving a multiplexed signal obtained by multiplexing a plurality of communication signals from a multiplexed signal transmitting section, demultiplexing the signal into communication signals, and transmitting the demultiplexed communication signal to a communication signal receiving section, comprising:

adding, to each of the communication signals, an identification address preassigned to a predetermined signal identifying section through which a communication signal passes in a multiplexing system including the multiplexed signal transmitting section and the communication signal receiving section, and outputting each of the communication signals;

extracting the identification address from the output signal; and

demultiplexing the multiplexed signal for each of the communication signals on the basis of the extracted identification address.

4. (Previously presented) A method according to claim 3, wherein the communication signal includes a PPP packet created for each Internet subscriber apparatus, and the identification address includes a MAC address.

5. (Previously presented) A demultiplexing method of demultiplexing a multiplexed signal obtained by multiplexing a plurality of packets into packets, comprising:

extracting an IP address from each packet in the received multiplexed signal; and

demultiplexing the multiplexed signal into PPP packets on the basis of the extracted IP addresses.

6-7. (Canceled).

8. (Original) A demultiplexing apparatus which is connected to a multiplexed signal transmitting section through a multiplex communication path, demultiplexes a multiplexed signal received from the multiplex communication path, and transmits demultiplexed communication signals to a communication signal receiving section through communication paths for the respective communication signals, comprising:

address extracting means, connected to the multiplex communication path, for extracting an identification address, for each of the communication signals, which is added to each of the communication signals in the multiplexed signal received from the multiplex communication path and preassigned to a predetermined signal identifying section through which a communication signal passes in a demultiplexing section including said multiplexed signal transmitting section and said communication signal receiving section; and

demultiplexing means for demultiplexing the multiplexed signal into the respective communication signals on the basis of the identification addresses of the respective communication signals which are extracted by said address extracting means.

9. (Previously presented) An apparatus according to claim 8, wherein the communication signal includes a PPP packet created for each Internet subscriber apparatus, and the identification address includes a MAC address.

10. (Original) A demultiplexing apparatus which is connected to a multiplex communication path through which a multiplexed signal obtained by multiplexing packets addressed to subscriber apparatuses is transmitted, demultiplexes the multiplexed signal received from the multiplex communication path, and outputs each demultiplexed communication signal, comprising:

address extracting means, connected to the multiplex communication path, for extracting an IP address of each packet in the multiplexed signal received from the multiplex communication path; and

demultiplexing means for demultiplexing the multiplexed signal into the respective packets on the basis of the IP addresses of the respective packets extracted by said address extracting means.

11. (Previously presented) An access network system comprising:

a plurality of subscriber apparatuses which transmit/receive one of a signal having a MAC address added to a packet and a signal having no MAC address added to a packet;

a subscriber multiplexing/demultiplexing apparatus which multiplexes packets in signals transmitted from said respective subscriber apparatuses on the basis of MAC addresses added to the packets or IP addresses of the packets, and demultiplexes an input multiplexed signal into packets on the basis of one of a MAC address added to each packet and an IP address of each packet; and

a protocol termination apparatus which includes a first interface block which interfaces with a backbone network, second and third interface blocks which interface a multiplexed signal with said subscriber multiplexing/demultiplexing apparatus, switching means, and PPP processing means,

wherein said protocol termination apparatus, when a packet in a multiplexed signal received from said subscriber multiplexing/demultiplexing apparatus through said second interface block includes a data packet, said protocol termination apparatus causes said switching means to switch to transfer the data packet to said first interface block on the basis of one of a MAC address added to the data packet and an IP address of the packet, and transmits the packet to a backbone network upon converting the packet into a POS signal by using said first interface block, and

when a packet in a multiplexed signal received from said subscriber multiplexing/demultiplexing apparatus through said second interface block includes a control packet, said protocol termination apparatus causes said switching means to switch to transfer the control packet to said PPP processing means on the basis of one of a MAC address added to the control packet and an IP address of the packet, and causes said PPP processing means to transmit the received control packet through said third interface block and perform PPP processing with said subscriber apparatus through said subscriber multiplexing/demultiplexing apparatus.

12. (Previously presented) A system according to claim 11, wherein the packet includes one of an Ethernet frame packet and an IEEE 802.3 frame packet, the data packet includes one of a PPP data packet in the Ethernet frame packet and a PPP data

packet in the IEEE 802.3 frame, and the control packet includes one of a PPP control packet in the Ethernet packet and a PPP control packet in the IEEE 802.3 frame.

13. (Previously presented) A system according to claim 11, wherein the packet includes one of a PPP packet in an Ethernet frame packet and a PPP packet in an IEEE 802.3 frame packet, the data packet includes one of a PPP data packet in the Ethernet frame packet and a PPP data packet in the IEEE 802.3 frame, and the control packet includes one of a PPP control packet in the Ethernet packet and a PPP control packet in the IEEE 802.3 frame.

14. (Previously presented) An access network system comprising:

a plurality of subscriber apparatuses which transmit/receive one of a signal having a MAC address added to a packet and a signal having no MAC address added to a packet;

a subscriber multiplexing/demultiplexing apparatus which multiplexes packets in signals transmitted from said respective subscriber apparatuses on the basis of MAC addresses added to the packets or IP addresses of the packets so as to output a multiplexed signal as a POS signal, and demultiplexes an input POS signal into packets on the basis of IP addresses of the packets;

an interface which is connected to said subscriber multiplexing/demultiplexing apparatus and transmits a POS signal; and

a protocol termination apparatus which includes a first interface block for interfacing with a backbone network, second and third interface blocks connected to said interface to interface a multiplexed signal with said subscriber multiplexing/demultiplexing apparatus, switching means, and PPP processing means,

wherein, when a packet in a multiplexed signal received from said subscriber multiplexing/demultiplexing apparatus through said second interface block includes a data packet, said protocol termination apparatus causes said switching means to switch so as to transfer the data packet to said first interface block on the basis of an IP address of the data packet, and transmits the packet to the backbone network upon converting the packet into a POS signal by using said first interface block,

when a packet in a POS signal received from said subscriber multiplexing/demultiplexing apparatus through said second interface block includes a control packet, said protocol termination apparatus causes said switching means to switch so as to transfer the control packet to said PPP processing means on the basis of an IP address of the control packet, and causes said PPP processing means to transmit the received control packet through said third interface block and perform first PPP processing as PPP processing between said subscriber apparatuses through said subscriber multiplexing/demultiplexing apparatus, and

said protocol termination apparatus transmits a control packet through said second interface block to perform second PPP processing as PPP processing between said protocol termination apparatus and said subscriber multiplexing/demultiplexing apparatus.

15. (Previously presented) A system according to claim 14, wherein the packet processed by said subscriber apparatus and the packets multiplexed by said subscriber multiplexing/demultiplexing apparatus include one of Ethernet frame packets and IEEE 802.3 frame packets, and the packets demultiplexed by said subscriber multiplexing/demultiplexing apparatus and the packet processed by said protocol

termination apparatus include PPP packets in PPP packet in PPP packets in an SDH/SONET frame transmitted over a POS signal.

16. (Previously presented) A system according to claim 14, wherein each of the packets processed by said subscriber apparatus and the packets multiplexed by said subscriber multiplexing/demultiplexing apparatus includes a packet selected from the group consisting of an Ethernet packet, an IEEE 802.3 packet, and a PPP packet in the packet, and one of Ethernet frame packets and IEEE 802.3 frame packets, the packets demultiplexed by said subscriber multiplexing/demultiplexing apparatus and the packet processed by said protocol termination apparatus include PPP packets in PPP packet in PPP packets in an SDH/SONET frame transmitted over a POS signal.

17-22. (Canceled).

23. (Previously presented) A protocol termination apparatus including a first interface block which converts a data packet into a POS signal and transmits the signal to a backbone network, a second interface block which is connected to a subscriber multiplexing/demultiplexing apparatus to which a subscriber apparatus is connected, and receives a transmitted multiplexed signal obtained by causing said subscriber multiplexing/demultiplexing apparatus to multiplexed signals which serve to transmit packets created for the respective subscriber apparatuses and are received from the subscriber apparatuses, and a third interface block connected to said subscriber multiplexing/demultiplexing apparatus, comprising:

said second interface block which extracts the packet and the MAC address added to one of the packet and an IP address of the packet from the multiplexed signal;

PPP processing means which is connected to said subscriber multiplexing/demultiplexing apparatus through said third interface block and performs PPP processing between the subscriber apparatuses through said subscriber multiplexing/demultiplexing apparatus; and

switching means for, when a packet extracted by said second interface block includes a data packet, transferring the data packet to said first interface block on the basis of one of the MAC address and the IP address of the packet which is extracted by said second interface block, and when a packet extracted by said second interface block includes a control packet, transferring the control packet to said PPP processing means on the basis of one of the MAC address and the IP address of the packet which are extracted by said second interface block.

24. (Previously presented) An apparatus according to claim 23, wherein the packet includes one of an Ethernet frame packet and an IEEE 802.3 frame packet.

25. (Previously presented) An apparatus according to claim 23, wherein the packet includes one of a PPP packet in an Ethernet frame packet and a PPP packet in an IEEE 802.3 frame packet.

26. (Previously presented) A protocol termination apparatus including a first interface block which converts a packet into a POS signal and transmits the signal to a backbone network, a second interface block which is connected, through an interface, to a

subscriber multiplexing/demultiplexing apparatus to which a subscriber apparatus is connected, and receives a transmitted multiplexed signal obtained by causing said subscriber multiplexing/demultiplexing apparatus, which has received signals, from the respective subscriber apparatuses, which are used to transmit packets created by the respective subscriber apparatuses, to multiplex the packets, and a third interface block connected to said subscriber multiplexing/demultiplexing apparatus, said interface being a interface which transmits a POS signal, comprising:

said second interface block which extracts a packet in the POS signal and an IP address of the packet;

PPP processing means, connected to said subscriber multiplexing/demultiplexing apparatus through said third interface block, for transmitting a control packet through said third interface block to perform first PPP processing as PPP processing between the subscriber apparatuses through said subscriber multiplexing/demultiplexing apparatus, and transmitting the control packet through said third interface block to perform second PPP processing as PPP processing with said subscriber multiplexing/demultiplexing apparatus; and

switching means for, when a packet extracted by said second interface block includes a data packet, transferring the data packet to said first interface block on the basis of the IP address extracted by said second interface block, and when a packet extracted by said second interface block includes a control packet, transferring the control packet to said PPP processing means on the basis of the IP address extracted by said second interface block.

27. (Previously presented) An apparatus according to claim 26, wherein the packet includes a PPP packet in a PPP packet in PPP packet in an SDH/SONET frame transmitted over an POS signal.